



# MixRite™

AGRICULTURE | GREENHOUSE | LANDSCAPE

No electricity needed, uses only water pressure to operate

Accurate proportioning regardless of water flow or pressure changes

Replaceable seals require no special tools and free seal kit included with each unit

UV resistant materials

Years of field use in a variety of conditions and applications



Efficient engine design results in minimal pressure loss

10% to 25% more flow than competitive models

Models for injection rates from .1% to 10% with water flow from .08-110 gpm

Models designed to withstand aggressive additives including PVDF models for strong acids and chlorine

**DEMA**®

10020 Big Bend BLVD, St. Louis, MO 63122, Tel: 314-966-3533  
Fax: 314-965-8319 [www.demaeng.com](http://www.demaeng.com) E-mail: [sales@demaeng.com](mailto:sales@demaeng.com)





# MixRite Models

## TF-5

TF-5-001: Rate of additive: 0.1% to 1%  
 TF-5-002: 0.2% to 2%  
 TF-5-005: 1% to 5%  
 Water pressure from 14.7 to 120 PSI (1-8 bar)  
 Flow Rate from 0.1 to 22 GPM (0.2-5 m<sup>3</sup>/h)  
 Weight: 13.2 Lbs (6.0 kg)  
 Coupling: 1" or 32 mm  
**10% more flow than the competition**

## TF-10

TF-10-001: Rate of additive: 0.1% to 1%  
 TF-10-002: 0.2% to 2%  
 TF-10-005: 1% to 5%  
 Water pressure from 14.7 to 120 PSI (1-8 bar)  
 Flow Rate from 2 to 45 GPM (0.5-10 m<sup>3</sup>/h)  
 Weight: 16.23 Lbs (7.38 kg)  
 Coupling: 1.5" or 50 mm  
**25% more flow than the competition**

## TF-25

TF-25-001: Rate of additive: 0.1% to 1%  
 TF-25-002: 0.3% to 2.5%  
 TF-25-005: 1% to 5.5%  
 Water pressure from 14.7 to 120 PSI (1-8 bar)  
 Flow Rate from 9 to 110 GPM (2-25 m<sup>3</sup>/h)  
 Weight: 46.42 Lbs (21.10 kg)  
 Coupling: 2" or 63 mm  
**25% more flow than the competition**



Includes maintenance wrench for easy access and seal replacement